



## FIREIDEPARTMENT

March 2000 REV January 2009

## UC DAVIS FIRE DEPARTMENT SELF INSPECTION CHECKLIST

Safety Coordinator:	Department:		
Phone:			
Date of Inspection:	Floor or Area:		
1. EXITING		ОК	Not OK
B. Corridors-Storage	e of any kind is not permitted e of any kind, regardless of not permitted unless specifically		
C. Exit Doors-Must Must not be block inoperable unless	plations or in writing by the UCD Fire Departure, close and latch properly.  ked, propped open or rendered specifically permitted in writing by	artment.	
•	ust not be damaged. arly signed and illuminated. up) lights operate properly		
	ALS Cylinders-Must be secured with opproved method, and clearly		
identified. EH&S B. Flammable/Com	•		
safety containers	al shipping containers or approved (maximum 5 gallons). Total aggregate		
D. Dispensing-Dispensing-Dispension of pallons is not p	fety containers must not exceed 25 gallons ensing from containers exceeding ermitted unless using a listed pump		
Annual permit m  E. Quantities in exce containers, or green	th California Fire Code requirements. ust be obtained from UC Fire Department. ess of 10 gallons and not in safety eater than 25 gallons in safety containers, a Flammable Liquid Storage Cabinet.		

R SYSTEM		
		$\Box$
		Ш
		П
NGUISHERS		
een charged area, (except CO2 extinguishers which		
· ·		
	`. 	$\Box$
ondiny hispection by building safety coordinator.		Ш
		Ш
re nose cabinets (generally in corridors) is unobstructed.		
	_	_
		Ш
	ning	
	_	
		$\Box$
* *		Ш
		П
	Ħ	Ħ
1.OK for use less than 90 days		
2.Surge suppressors OK for use with computer equip.		
authorized in writing by the UC Fire Department		
ENOUS		
• • • • • • • • • • • • • • • • • • • •		$\overline{}$
		Ш
eidental activation of smoke detectors.	Provent	
	cess to standpipes (generally located in stairwell), re hose cabinets (generally in corridors) is unobstructed.  CONTAINERS of permitted in or exposed to corridor unless CD Fire Department approved, UL Listed, self-extinguish ontainer and is located/secured in an alcove or other rea not obstructing exit path. aterial does not exceed capacity of container.  CAL three (3) Foot working space is maintained in front of all rectrical panels. rectrical outlet covers are in place and not broken rexposed wiring. re of extension cords or temporary power taps: 1.OK for use less than 90 days 2.Surge suppressors OK for use with computer equip. 3.All other uses not permitted unless specifically authorized in writing by the UC Fire Department.  AENOUS ange in occupancy or use. Changes in how a room or ray is used must be reviewed by the Fire Department. amples include office to laboratory; office to meeting om; classroom to laboratory; etc. nstruction-Modifications to buildings, rooms or areas red to be reviewed by the Fire Department. Examples include office to modifications to buildings, rooms or areas red to be reviewed by the Fire Department. Examples include office to modifications, which involve painting, etc., do not riew by the Fire Department, but may need coordination to	erify there are not any decorations or any attachments to minklers or associated piping. orage is maintained 18" below ceiling and below ceiling in unsprinklered buildings rinklers in need of replacement (damaged, proded, painted).  NGUISHERS  The extinguishers are accessible, the gauge reads in the reen charged area, (except CO2 extinguishers which in't have a gauge), serviced within last 12 months, binet door is operable, extinguisher mounted within in' of floor to not more than 5 feet from top of extinguisher. Onthly inspection by building safety coordinator.  ES  CCES ccess to standpipes (generally located in stairwell), re hose cabinets (generally in corridors) is unobstructed.  CONTAINERS  of permitted in or exposed to corridor unless  CD Fire Department approved, UL Listed, self-extinguishing ontainer and is located/secured in an alcove or other rea not obstructing exit path.  aterial does not exceed capacity of container.  CAL  three (3) Foot working space is maintained in front of all extrical panels.  Extrical panels.  Extrical outlet covers are in place and not broken provided wiring.  The exposed wiring.  The of extension cords or temporary power taps:  1.0K for use less than 90 days  2. Surge suppressors OK for use with computer equip.  3. All other uses not permitted unless specifically authorized in writing by the UC Fire Department.  SENOUS  ange in occupancy or use. Changes in how a room or a is used must be reviewed by the Fire Department.  AENOUS  ange in occupancy or use. Changes in how a room or a is used must be reviewed by the Fire Department.  ENOUS  ange in occupancy or use. Changes in how a room or a is used must be reviewed by the Fire Department.  Exercical panels, contracting rooms, etc., shetic modifications, which involve painting, etc., do not need riew by the Fire Department, but may need coordination to prevent

Please complete the following page with remarks for any items that were checked "not OK" with a plan for correction of the deficiencies. If a work order is placed please proved number.

REMARKS AND PLAN OF CORRECTION:				

UCD FireNet: Self Inspection Checklist REV. 1/09